


3 Phase Sump To OHT

 Start Button

 Stop Button

Remove jumper wire between start and stop button



INTRODUCTION:

TRANSMITTER: The unit is placed near the overhead water tank.

Connect the transmitter unit to the power supply.

Totally two sensors are used here, these sensors only detect the water level in the tank and send it to the transmitter from there the signal is transferred to the receiver.

RECEIVER: The unit is placed near the motor.

When the signal received is received from the transmitter, the receiver starts the operation.

If the water crosses the LOW LEVEL sensor in the tank, then it detect and transmit the signal to the receiver through the transmitter, the motor start running still it reaches the TOP LEVEL sensor .

Once the water filled in the tank the TOP LEVEL sensor detect and transmit the signal to the receiver through the transmitter, then the motor return to OFF STATE.

COLOUR CODE: for connecting wires

RED-TOP

BROWN-LOW

BLACK:GROUND OF TWO SENSORS

STATUS: when the water reaches below the bottom level, both the sensors becomes off mode, the motor gets started

OHT TOP: yellow led OFF

OHT LOW: red led OFF

MOTOR: starts ON

STATUS: when the water in the tank once reaches the top level, the motor will stop. The top and bottom level will start glowing

OHT TOP: yellow led GLOW



OHT LOW: red led GLOW

MOTOR: returns OFF state

STATUS: Switches OFF the pump when the water level reaches the minimum level in the underground tank therefore prevent motor life.

This is indicated by only UNIT ON led (red) only glow.

Shall again switch ON the Pump when there is Sufficient Water in the Underground Tank [SUMP], this is indicated by sump indication(red).



SUMP TANK

APPLICATION:

Automatic Water level Controller for Hotels, Factories, Home, Apartment, Commercial Complexes, Drainage, etc.,

It can be fixed for single phase motor, Single Phase Submersibles, Three Phase motor (For 3 Phase and Single Phase Submersible Starter is necessary) and open well, Bore well and Sump.

ADVANTAGES:

Easy installation.

Compact and elegant design.

Saves water, power and energy.

Avoids seepage of water from roofs and walls due to overflowing tanks.

Fully automatic.